

Propow — the Expert Power Solution for Electric 2 & 3-Wheelers.

Longer Range, Longer Life, Faster Charging



Longer Lifespan Up to 10 years design life.



Charge Less, Ride More Fast-charging, long-range lithium batteries.



Remote Diagnostic and Remote Upgrades Optional Smarter lithium technology for safer, farther, and faster journeys.



Bluetooth Monitoring Optional Easy access to battery status via mobile.



Built-in Heating Optional
Reliable performance in cold conditions.



IP67 Waterproof
Built for tough outdoor conditions.



Ultra SafeBuilt-in BMS protection.



5 Year warranty





UN38.3

Power Your Ride with Safety, Endurance & Speed

Advanced LiFePO4 Battery Solutions for E-Bikes & E-Trikes Lithium Power for Your Ride

Stronger Smarter Faster









48V 20Ah

Electrical Specifications Nominal voltage: 51.2V

Nominal capacity: 20Ah Energy: 1024Wh Cycle life: >4,000 cycles Connect in parallel: Yes

Bluetooth: Yes, customized bluetooth APP acceptable Remote diagnostics and upgrades: Optional

Pre-Heating system: Optional

Dimensions (L x W x H): 180*155*210mm 7.09x6.1x8.27"

Weight: 9.5KG(20.94lb)

Case material & IP rating: Steel, IP67

Charge current: 20A Continuous discharge current: 20A Peak discharge current: 40A(5s)

Max. charge voltage: 58.4V Cut-off voltage: 40V

Battery management system(BMS): Yes, built-in BMS protection



48V 100Ah

Electrical Specifications Nominal voltage: 51.2V Nominal capacity: 100Ah Energy: 5120Wh Cycle life: >4,000 cycles

Connect in parallel: Yes

Smart & Safe LiFePO4 Technology

Bluetooth: Yes, customized bluetooth APP acceptable Remote diagnostics and upgrades: Optional

Pre-Heating system: Optional

Dimensions (L x W x H): 410*285*237mm 16.14x11.22x9.33"

Weight: 50KG(110.23lb)

Case material & IP rating: Steel, IP67

Charge current: 100A

Continuous discharge current: 100A Peak discharge current: 200A(5s) Max. charge voltage: 58.4V

Cut-off voltage: 40V

Battery management system(BMS): Yes, built-in BMS protection

for Modern Mobility

-Longer Ride Distance

-Faster Charging

-Consistent Power

-Rugged & Reliable

-Real-time Monitoring

-Ultra Safe



60V 20Ah

Electrical Specifications Nominal voltage: 60.8V Nominal capacity: 20Ah Energy: 1216Wh Cycle life: >4,000 cycles

Connect in parallel: Yes

Bluetooth: Yes, customized bluetooth APP acceptable Remote diagnostics and upgrades: Optional

Pre-Heating system: Optional

Dimensions (L x W x H): 180*155*255mm 7.09x6.1x10.04"

Weight: 11KG(24.25lb)

Case material & IP rating: Steel, IP67

Charge current: 20A

Continuous discharge current: 20A Peak discharge current: 40A(5s) Max. charge voltage: 69.35V Cut-off voltage: 47.5V

Battery management system(BMS): Yes, built-in BMS protection



60V 45Ah

Electrical Specifications

Nominal capacity: 45Ah Energy: 2736Wh Cycle life: >4,000 cycles Connect in parallel: Yes


Bluetooth: Yes, customized bluetooth APP acceptable

Pre-Heating system: Optional

Dimensions (L x W x H): 255*167*330mm 10.04x6.57x13"

Charge current: 45A Continuous discharge current: 50A

Battery management system(BMS): Yes, built-in BMS protection



60V 150Ah

Electrical Specifications Nominal voltage: 60.8V Energy: 9120Wh

Bluetooth: Yes, customized bluetooth APP acceptable Remote diagnostics and upgrades: Optional

Case material & IP rating: Steel, IP67

Charge current: 100A Continuous discharge current: 100A

Cut-off voltage: 47.5V



72V 30Ah

Electrical Specifications Nominal voltage: 73.6V

Nominal capacity: 30Ah Energy: 2208Wh Cycle life: >4,000 cycles Connect in parallel: Yes

Bluetooth: Yes, customized bluetooth APP acceptable Remote diagnostics and upgrades: Optional Pre-Heating system: Optional

Dimensions (L x W x H): 215*167*315mm 8.46x6.57x12.4"

Weight: 19KG(41.89lb)

Case material & IP rating: Steel, IP67 Charge & Discharge Charge current: 30A

Continuous discharge current: 30A Peak discharge current: 60A(5s) Max. charge voltage: 83.95V

Cut-off voltage: 57.5V Battery management system(BMS): Yes, built-in BMS protection

Nominal capacity: 150Ah Cycle life: >4,000 cycles

Connect in parallel: Yes

Pre-Heating system: Optional

Dimensions (L x W x H): 500*370*235mm 19.69x14.57x9.25"

Weight: 89KG(196.2lb)

Peak discharge current: 200A(5s) Max. charge voltage: 69.35V

Battery management system(BMS): Yes, built-in BMS protection

PROPOW 72V 50Ah

72V 50Ah

Electrical Specifications Nominal voltage: 73.6V Nominal capacity: 54Ah Energy: 3974.4Wh

Cycle life: >4,000 cycles Connect in parallel: Yes

Bluetooth: Yes, customized bluetooth APP acceptable Remote diagnostics and upgrades: Optional Pre-Heating system: Optional

Dimensions (L x W x H): 315*280*295mm 12.5x11.2x11.6"

Weight: 38KG(83.78lb) Case material & IP rating: Steel, IP67

Charge & Discharge S Charge current: 50A

Continuous discharge current: 50A Peak discharge current: 100A(5s) Max. charge voltage: 83.95V

Cut-off voltage: 57.5V Battery management system(BMS): Yes, built-in BMS protection



72V 105Ah

Electrical Specifications Nominal voltage: 73.6V

Nominal capacity: 105Ah Energy: 7728Wh Cycle life: >4,000 cycles Connect in parallel: Yes

Bluetooth: Yes, customized bluetooth APP acceptable Remote diagnostics and upgrades: Optional Pre-Heating system: Optional

Dimensions (L x W x H): 526*280*235mm 20.71x11.02x9.25"

Weight: 70KG(154.3lb) Case material & IP rating: Steel, IP67

Charge & Discharge S Charge current: 100A

Continuous discharge current: 100A Peak discharge current: 200A(5s) Max. charge voltage: 83.95V Cut-off voltage: 57.5V

Battery management system(BMS): Yes, built-in BMS protection



Nominal voltage: 60.8V

Remote diagnostics and upgrades: Optional

Weight: 23KG(50.7lb)
Case material & IP rating: Steel, IP67

Peak discharge current: 100A(5s) Max. charge voltage: 69.35V Cut-off voltage: 47.5V



72V 20Ah

Electrical Specifications Nominal voltage: 73.6V Nominal capacity: 20Ah Energy: 1472Wh Cycle life: >4,000 cycles Connect in parallel: Yes

Bluetooth: Yes, customized bluetooth APP acceptable

Remote diagnostics and upgrades: Optional Pre-Heating system: Optional

Dimensions (L x W x H): 180*155*300mm 7.09x6.1x11.8" Weight: 13.5KG(29.8lb)

Case material & IP rating: Steel, IP67

Charge current: 20A Continuous discharge current: 20A Peak discharge current: 40A(5s) Max. charge voltage: 83.95V

Cut-off voltage: 57.5V

Battery management system(BMS): Yes, built-in BMS protection



72V 150Ah

Electrical Specifications Nominal voltage: 73.6V

Nominal capacity: 150Ah Energy: 11040Wh Cycle life: >4,000 cycles Connect in parallel: Yes

Bluetooth: Yes, customized bluetooth APP acceptable Remote diagnostics and upgrades: Optional

Pre-Heating system: Optional

Dimensions (L x W x H): 580*370*235mm 22.83x14.57x9.25"

Weight: 89KG(196lb)

Case material & IP rating: Steel, IP67

Charge & Discharge S Charge current: 100A

Continuous discharge current: 100A Peak discharge current: 200A(5s) Max. charge voltage: 83.95V

Cut-off voltage: 57.5V

Battery management system(BMS): Yes, built-in BMS protection

